
Grille Nordic version

DGAN



Description

The opposed blade damper DGAN can be fitted to the AD, AE, AL, AR and AC aluminium grilles.

The opposed blade damper is held in place by clips, for fixing the damper to the grille.

The DGAN dampers are made entirely of galvanized steel and have mechanism for opening and closing all the damper blades simultaneously (by using a screwdriver).

DGAN is provided with spring wire to prevent the blades from clattering.


Maintenance

Remove the grille to gain access to the opposed blade damper or duct. External parts should be wiped with a damp cloth.

Materials and finish


Opposed blade damper: Galvanized steel

Order code - Nordic version



Example: DGAN -400 - 150

Min. - max. dimensions




DGAN in combination with hidden screw installation.

| H L | 6 | 00 | + | 10 | 00 | + + | 1200 | | |
|------|--|----|----------|----|----|------------|------|--|--|
| 300 | Compatible with DGAN Not compatible with DGAN | | | | | | | | |
| 600 | | | | | | | | | |
| 1000 | | | | | | | | | |
| | | | | | | | | | |

Standard dampers are available in steps of 50 mm within the above min. and max. sizes.

Customized sizes available on request.



Grille with 1 row of blades

Grille with 2 rows of blades



Grille installation type CN, CMN, V, VMN. A full length click on DGAN damper is available.



Grille installation type H and HMN. The grille will have a shortend length DGAN damper option due to the hidden screw or bridge (AL) installation.

The damper is mounted from factory and is not detachable. x = 51 mm

